
Ordering of a non-standard switch

Appendix no. for the order no. for non-standard assemblies

Type of switch	Mounting method	Protection level	Knob and plate for ŁK		
SK10pcs	☐ To the panel	□ IP41			
SK16pcs	☐ To the base	□ IP65			
SK20pcs	☐ Snap mounting on TS35 rail				
SK25pcs	☐ Enclosure				
SK32pcs	☐ Assembly A				
SK40pcs	☐ Assembly A30				
SK63pcs					
SK100pcs					
ŁK16Rpcs					
ŁK25Rpcs					
ŁK32Rpcs					
ŁK15pcs					
ŁK40pcs					
ŁK63pcs					

Switching diagram								
Jumper bars,	Rotation angle							
bridges								
Contacts	Switching							
1-2								
3-4								
5-6								
7-8								
9-10								
11-12								
13-14								
15-16								
17-18								
19-20								
21-22								
23-24								
25-26								
27-28								
29-30								
31-32								
33-34								
35-36								
37-38								
39-40								



Ordering of a non-standard switch

Note about ordering

When ordering standard ŁK and SK switches, please select the amperage, type, assembly and mounting method.

Examples:

1) **SWITCH ŁK40-2.829\P**

Disconnector for currents up to 40A (ŁK40), type 0-l, 3-way with auxiliary circuit (assembly no. 2.829), panel mounting (P)

2) **SWITCH ŁK40-2.829\OB2Z**

Disconnector for currents up to 40A (ŁK40), type 0-l, 3-way with auxiliary circuit (assembly no. 2.829), in an enclosure with a legend plate, lockable (OB2Z) with two glands

Example of a switching diagram

Switching diagram														
Jumper bars,		,	Rotation angle											
	bridges		45	0	45									
	Contacts		Switching											
	1-2		X											
	3-4		X											
	5-6	١		X	X									
	7-8			X										
	9-10				X									
	11-12				X									
	13-14		X		X									
	15-16													
	17-18	1	X	\times										
	19-20			\times										
	21-22			X	X									
	23-24													
	25-26													
	27-28													
	29-30													
	31-32													
	33-34													
	35-36													
	37-38													
	39-40													