

## Mikrospínač, zahnutá kladka s rolkou MS \ 1743




## Složení objednáacího kódu

MS\1743

## Popis výrobku

- Various of actuators, action position is adjustable
- High switch on and off capacity(15A)
- High accuracy
- Wide range of operation speed

## Funkce kontaktů



## Parametry

Rated voltage	Noninductive Load (A)				Inductive Load (A)				Inrush Current	
	Resistance Load		Lamp Load		Inductive Load		Motor Load			
	NC	NO	NC	NO	NC	NO	NC	NO	NC	NO
125VAC	15		3	1.5	15	5	2.5			
250VAC	15		2.5	1.25	15	3	1.5			
500VAC	3		1.5	0.75	2.5	1.5	0.75			
8VDC	15		3	1.5	15	5	2.5	max 30	max 15	
14VDC	15		3	1.5	10	5	2.5			
30VDC	6(2)		3	1.5	5	5	2.5			
125VDC	0.4		0.4	0.4	0.05	0.05	0.05			
250VDC	0.2		0.2	0.2	0.03	0.03	0.03			

## Technické parametry

Maximální počáteční síla	160 g
Minimální uvolňovací síla	42 g
Maximální počáteční pojezd	2,7 mm
Minimální horní posun	2,4 mm
Maximální diferenciální posun	0,5 mm
Maximální volná pozice	43,6 mm
Pracovní poloha	43,1±0,8

