

## Łącznik krańcowy (tworzywo) awaryjnego stopu LK\293



## Ordering code

LK\293

## Ratings

Rated voltage	Noninductive Load (A)				Inductive Load (A)			
	Resistance Load		Lamp Load		Inductive Load		Motor Load	
	NC	NO	NC	NO	NC	NO	NC	NO
125VAC	10		3	1.5	10		5	2.5
250VAC	10		2.5	1	10		3	1.5
400VAC	10		1.5	0.8	3		1.5	0.8
8VDC	10		6	3	10		6	6
14VDC	10		6	3	10		6	6
30VDC	6		4	3	6		4	4
125VDC	0.8		0.2	0.2	0.8		0.2	0.2
250VDC	0.4		0.1	0.1	0.4		0.1	0.1

## Technical data

Rating	A 240VAC (A300)
Ambient temperature	-10 ... +70°C (with no icing)
Protection level	IP65
Rated insulation voltage $U_i$	400V
Insulation resistance	100mΩ min. (at 500VDC)
Operation speed	0.1m ~0.5m/s
Operating frequency	30 operations/minute
Shock	Mechanical: Approx. 1000m/s <sup>2</sup> (Approx. 100G'S) Electrical: Approx. 300m/s <sup>2</sup> (Approx. 30G'S)
Humidity	< 95% RH
Live	Mechanical: 10,000,000 operations/min. Electrical: 150,000 operations/min.
Dielectric strength	AC2500V/Umpic 4KV

## Accessories

LK\293-H Głowica awaryjnego stopu do łącznika krańcowego

## Dimensions

