

Cam switch in enclosure with lamp SK16 OB11L



Ordering code

SK 16 - \


OB11/L in housing OB11 with green indicator lamp 230AC
OB11C/L in housing OB11 with yellow-red front and green indicator lamp 230AC
OB11Z/L in housing OB11 with lockable front and green indicator lamp 230AC
OB11ZC/L in housing OB11 with lockable yellow-red front and green indicator lamp 230AC

Assembly number

1.825 Disconnecter 0-1 (1 - pole)
1.828 Disconnecter 0-1 (2 - pole)
2.8211 Disconnecter 0-1 (3 - pole)
2.8210 Disconnecter 0-1 (4 - pole)
3.8220 Disconnecter 0-1 (5 - pole)
3.8210 Disconnecter 0-1 (6 - pole)
4.8240 Disconnecter 0-1 (7 - pole)
4.824 Disconnecter 0-1 (8 - pole)

Current
16 16 A

Dimensions



Number of segments in the switch

1 ... 4

Gland type

M20x1,5

Technical data

Rated insulation voltage U_e	690 V
Rated withstand impulse voltage U_{imp}	6 kV
Rated continuous current $I_u=I_{th}$	20 A
Rated operational current I_e for AC-21A, AC-22A	16 A (230/400/500/690 V)
Rated operational power P_e for AC-23A	3 kW (230 V) 5 kW (400 V) 6 kW (500 V) 8 kW (690 V)
Rated operational power P_e for AC-3	2 kW (230 V) 3.5 kW (400 V) 4 kW (500 V) 6 kW (690 V)
Rated operational current I_e for DC-21A	16 A (24 V) 8 A (110 V) 6 A (220 V)
Short-time short-circuit withstand current $I_{cw}(1s)$	0.25 kA
Rated short-circuit making current I_{cm}	0.34 kA
Rated conventional short-circuit current	10 kA
Rated current fuse link gG	16 A
Wire gauge	1...4 mm ²
Tightening torque, terminals	0.5 Nm
Panel mounting	31/□36
Mechanical endurance	3.0 mln (transposition cycles)
Ambient temperature	-40 ... +70°C (work) -40 ... +70°C (storage)
Protection level: PN-EN 60529 to the panel	IP65
Protection level of OB enclosure	IP65
Vibration test (acc. to IEC 60068-2-6)	2...13, 2...100 Hz (frequency) ± 1 mm (acceleration amplitude) ±0.7 g (acceleration amplitude)
Shock test (acc. to IEC 60068-2-27)	15 g (peak acceleration) 11 ms (impulse duration)
Damp heat cyclic test (acc. to IEC 60068-2-30)	55°C (ambient temperature) 95% (relative humidity)
Salt mist cyclic test (acc. to IEC 60068-2-52)	severity 1