

## Cam switch in enclosure with lamp SK40 OB13L



### Ordering code

SK 40 -  \



**OB13/L** in housing OB13 with green indicator lamp 230AC  
**OB13C/L** in housing OB13 with yellow-red front and green indicator lamp 230AC  
**OB13Z/L** in housing OB13 with lockable front and green indicator lamp 230AC  
**OB13ZC/L** in housing OB13 with lockable yellow-red front and green indicator lamp 230AC

#### Mounting


#### Assembly number

**1.825** Disconnecter 0-1 (1 - pole)  
**1.828** Disconnecter 0-1 (2 - pole)  
**2.8211** Disconnecter 0-1 (3 - pole)  
**2.8210** Disconnecter 0-1 (4 - pole)  
**3.8220** Disconnecter 0-1 (5 - pole)  
**3.8210** Disconnecter 0-1 (6 - pole)  
**4.8240** Disconnecter 0-1 (7 - pole)  
**4.824** Disconnecter 0-1 (8 - pole)

#### Current

40 40 A

### Dimensions



### Number of segments in the switch

1 ... 4

### Gland type

M25x1,5

## Technical data

Rated insulation voltage $U_e$	690 V
Rated withstand impulse voltage $U_{imp}$	6 kV
Rated continuous current $I_u=I_{th}$	50 A
Rated operational current $I_e$ for AC-21A, AC-22A	40 A (230/400/500/690 V)
Rated operational power $P_e$ for AC-23A	9 kW (230 V) 15 kW (400 V) 18.5 kW (500 V) 26 kW (690 V)
Rated operational power $P_e$ for AC-3	7.5 kW (230 V) 12 kW (400 V) 15 kW (500 V) 21 kW (690 V)
Rated operational current $I_e$ for DC-21A	40 A (24 V) 20 A (110 V) 15 A (220 V)
Short-time short-circuit withstand current $I_{cw}(1s)$	0.5 kA
Rated short-circuit making current $I_{cm}$	0.7 kA
Rated conventional short-circuit current	10 kA
Rated current fuse link gG	50 A
Wire gauge	4...10 mm <sup>2</sup>
Tightening torque, terminals	1.2 Nm
Panel mounting	□48
Mechanical endurance	3.0 mln (transposition cycles)
Ambient temperature	-40 ... +70°C (work) -40 ... +70°C (storage)
Protection level: PN-EN 60529 to the panel	IP65
Protection level of OB enclosure	IP65
Vibration test (acc. to IEC 60068-2-6)	2...13, 2...100 Hz (frequency) ± 1 mm (acceleration amplitude) ±0.7 g (acceleration amplitude)
Shock test (acc. to IEC 60068-2-27)	15 g (peak acceleration) 11 ms (impulse duration)
Damp heat cyclic test (acc. to IEC 60068-2-30)	55°C (ambient temperature) 95% (relative humidity)
Salt mist cyclic test (acc. to IEC 60068-2-52)	severity 1